

**VALPRO COMMERCIAL REFRIGERATION**

203 Kelsey Ln., Building G

Tampa, FL 33619

813-502-0300

Toll Free 1-888-VALPRO-8

www.ValproRefrigeration.com

sales@ValproRefrigeration.com

PROJECT:

MODEL #:

ITEM #:

QTY:

AVAILABLE W/H:

APPROVAL:

**REACH-IN SOLID DOOR REFRIGERATOR**

MODEL: VP19R-HC

We are proud to introduce the beautifully constructed **Valpro VP19R-HC**. All our models are manufactured with uncompromising quality, energy efficient technology, and standard premium features built in. This model will provide many years of worry free service and delivers cost saving eco-friendly energy efficiency. All models are energy verified and deliver the lowest operating costs. All Valpro products are manufactured under strict ISO9001 standards for quality assurance, and to consistently deliver to our customers products that satisfy all expectations. All our products are operated, extensively monitored, and undergo rigorous inspection prior to packaging and shipping.

**KEY FEATURES**

- Durable stainless steel exterior, and 304 stainless interior cabinet
- High efficiency bottom mounted condensing unit installed on slide out rack for quick and easy maintenance
- Bottom mount compressor operates in coolest area possible and provides better efficiency and ergonomics
- Uniform temperature with larger efficient ECM fan motors and larger fan blades for superior air flow with faster recovery time
- 3 Heavy duty, epoxy coated wire shelves supported by pilasters for easy 1/2" adjustability and to sustain maximum loads
- Field reversible door
- Self closing door with remain open feature past 90° for easy access loading and unloading
- Top mount quality door lock for added security
- Snap-in magnetic door gaskets removable and replaceable without tools for ease of cleaning
- LED interior cabinet lights standard all on models
- Electronic thermostat digitally controlled temperature system maintains optimum temperature with easily viewed LED display
- Standard 4" heavy duty casters, front locking, make it easy to move and clean underneath
- Self-contained refrigeration system uses environmentally responsible hydrocarbon R290 refrigerant.
- Automatic condensate evaporation system
- Door integrated heating element eliminates any condensation
- High density 2.4" foamed in-place CFC free polyurethane insulation
- Energy Verified efficiency and ETL certified to NSF Standard 7



Intertek



Intertek

**WARRANTY**  
**2 YEAR Parts & Labor**  
**5 YEAR Compressor**

\* Compressor warranty 2 year parts & labor / 3 additional year warranty compressor part only

## Technical Data

### Dimensional Data

|                      |                          |
|----------------------|--------------------------|
| Exterior Dimensions  | 26.8"W x 25.6"D x 82.3"H |
| Interior Dimensions  | 22.2"W x 20.5"D x 50.2"H |
| Net Storage Capacity | 19 cu. ft.               |
| Net Weight           | 220 lbs.                 |
| Crated Weight        | 291 lbs.                 |
| Shipping Dimensions  | 29.9"W x 27"D x 84.6"H   |

### Refrigeration Data

|                        |                |
|------------------------|----------------|
| Temperature Range      | 33°F - 41°F    |
| Refrigerant            | R-290          |
| Refrigerating System   | Capillary Tube |
| Temperature Controller | Digital        |
| Horsepower             | 1/5            |

### Construction Data

|                         |                            |
|-------------------------|----------------------------|
| Exterior Material       | 430 Series Stainless Steel |
| Interior Floor Material | 304 Series Stainless Steel |
| Interior Wall Material  | 304 Series Stainless Steel |
| Insulation              | 2.4" CFC Free Polyurethane |
| Shelves                 | 3 Heavy Duty Epoxy Coated  |

### Electrical Data

|                             |               |
|-----------------------------|---------------|
| Interior Lighting           | Efficient LED |
| Amps                        | 3             |
| Voltage / Frequency / Phase | 115V/60Hz/1   |
| Plug Type                   | NEMA 5-15P    |
| Electrical Cord Length      | 8 ft.         |

Specifications subject to change without notice.

